Sarnavap® Self-Adhered Primer VC

Revision Date 12/20/2013

Print Date 12/20/2013

1. Identification

Product name	:	Sarnavap® Self-Adhered Primer VC
Supplier	:	Sika Corporation
Address	:	201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Recommended use of the chemical and restrictions on use	:	For further information, refer to the product technical data sheet.

2. Hazards identification

GHS Classification

Flammable liquids, Category 2 Eye irritation, Category 2A Specific target organ systemic toxicity single exposure, Category 3, Central nervous system H225: Highly flammable liquid and vapor.H319: Causes serious eye irritation.H336: May cause drowsiness or dizziness.

GHS Label element

Hazard pictograms

Hazard Statements

Signal Word



H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary Statements

- Prevention:
 P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 - P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.



Sarnavap[®] Self-Adhered Primer VC

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER or doctor/ physician if you feel unwell. P337 + P313 If eye irritation persists: Get medical advice/ attention. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Print Date 12/20/2013

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Warning : Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain,liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
methyl acetate	79-20-9	>= 25 - < 50 %
tert-butyl acetate	540-88-5	>= 25 - < 50 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled

Move to fresh air.

Consult a physician after significant exposure.

Sarnavap[®] Self-Adhered Primer VC

Povision	Date 12/20/2013	

R

Print Date 12/20/2013

In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	: irritant effects
uciayeu	Respiratory disorder Excessive lachrymation Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.
Protection of first-aiders	 Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
Notes to physician	: Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	Water High volume water jet	
Specific hazards during fire fighting	Do not use a solid water stream as it may scatter and sp fire.	bread
Specific extinguishing methods	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately must not be discharged into drains. Fire residues and contaminated fire extinguishing water be disposed of in accordance with local regulations.	
Special protective equipment for fire-fighters	In the event of fire, wear self-contained breathing appara	atus.

6. Accidental release measures



Revision Date 12/20/2013	Print Date 12/20/2013
Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	 Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. Handling and storage

Advice on safe handling	Do not breathe vapors or spray mist. Avoid exceeding the given occupational exposure limits (s section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Follow standard hygiene measures when handling chemic products.	
Conditions for safe storage	Store in original container. Store in cool place. Keep in a well-ventilated place. Containers which are opened must be carefully resealed a kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.	and
Materials to avoid	no data available	

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
methyl acetate	79-20-9	ACGIH	TWA	200 ppm
		ACGIH	STEL	250 ppm
		OSHA Z-1	TWA	200 ppm 610 mg/m3



Revision Date 12/20/2013

Print Date 12/20/2013

		OSHA P0	TWA	200 ppm 610 mg/m3
		OSHA P0	STEL	250 ppm 760 mg/m3
tert-butyl acetate	540-88-5	ACGIH	TWA	200 ppm
		OSHA Z-1	TWA	200 ppm 950 mg/m3
		OSHA P0	TWA	200 ppm 950 mg/m3

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**<u>Basis</u>

ACGIH. Threshold Limit Values (TLV) OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values) OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant OSHA P2. Permissible Exposure Limits (PEL), Table Z-2 OSHA Z3. Table Z-3, Mineral Dust

Engineering measures: Use of adequate ventilation should be sufficient to control
worker exposure to airborne contaminants. If the use of this
product generates dust, fumes, gas, vapor or mist, use
process enclosures, local exhaust ventilation or other
engineering controls to keep worker exposure below any
recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust
concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection	:	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
		The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection		
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Sarnavap® Self-Adhered Primer VC

Revision Date 12/20/2013	

Print Date 12/20/2013

Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	 Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove respiratory and skin/eye protection only after vapors have been cleared from the area. Remove contaminated clothing and protective equipment before entering eating areas.

9. Physical and chemical properties

Appearance	:	liquid
Color	:	red
Odor	:	solvent
Odor Threshold	:	no data available
Flash point	:	14 °F (-10 °C)
Ignition temperature	:	no data available
Decomposition temperature	:	no data available
Lower explosion limit (Vol%)	:	no data available
Upper explosion limit (Vol%)	:	no data available
Flammability (solid, gas)	:	no data available
Oxidizing properties	:	no data available
Autoignition temperature	:	no data available
рН	:	Note: not applicable
Melting point/range / Freezing point	:	no data available
Boiling point/boiling range	:	no data available
Vapor pressure	:	0.1 mmHg (0.1 hpa)
Density	:	0.940 g/cm3
Water solubility	:	Note: insoluble
Partition coefficient: n- octanol/water	:	no data available
Viscosity, dynamic	:	no data available
Viscosity, kinematic	:	ca.> 20.5 mm2/s



Sarnavap® Self-Adhered Primer VC

Print Date 12/20/2013

		at 104 °F (40 °C)
Relative vapor density	:	no data available
Evaporation rate	:	no data available
Burning rate	:	no data available
Volatile organic compounds (VOC) content	:	0 g/l with exemptions

10. Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
reactions	Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: no data available

11. Toxicological information

Acute toxicity

Product

Acute oral toxicity	:	no data available
Acute inhalation toxicity	:	no data available
Acute dermal toxicity	:	no data available

Skin corrosion/irritation

Product

no data available

Serious eye damage/eye irritation

Product

Causes serious eye irritation.

Respiratory or skin sensitization

Product

no data available

Sarnavap® Self-Adhered Primer VC

Revision Date 12/20/2013

Print Date 12/20/2013

Germ cell mutagenicity	
Product	
Mutagenicity	: no data available
Carainaganiaity	
Carcinogenicity	
Product	
Carcinogenicity	: no data available
IARC	not applicable
NTP	not applicable
Reproductive Toxicity/Fertility	
Product	
Reproductive toxicity	: no data available
Panraduativa Taviaitu/Davalanm	
Reproductive Toxicity/Developm	entreratogenicity
<u>Product</u>	
Teratogenicity	: no data available
STOT-single exposure	
Product	
Assessment: May cause drows	siness or dizziness.

STOT-repeated exposure

Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Product

Assessment: no data available

Aspiration toxicity

Product

no data available

12. Ecological information

Other information

Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Sarnavap® Self-Adhered Primer VC

Revision Date 12/20/2013

Print Date 12/20/2013

13. Disposal considerations

Disposal methods	
Waste from residues	: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT UN number Description of the goods Class Packing group Labels Emergency Response Guidebook Number	1133 Adhesives 3 II 3 128
IATA UN number Description of the goods Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passenger aircraft) Packing instruction (passenger aircraft)	1133 Adhesives 3 II 3 364 353 Y341
IMDG UN number Description of the goods Class Packing group Labels EmS Number 1 EmS Number 2	1133 ADHESIVES 3 II 3 F-E S-D
Marine pollutant	no

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b) IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

no data available





Print Date 12/20/2013

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

15. Regulatory information

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	Fire Hazard Acute Health Hazard
SARA 302 :	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313 :	SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Clean Air Act	
Ozone-Depletion Potential	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Air Act Section 12 (40 CFR 61)	any chemicals listed under the U.S. Clean Air Act Section 112(r) for
California Prop 65	This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

16. Other information



Revision Date 12/20/2013

Print Date 12/20/2013

HMIS Classification

Health	2
Flammability	3
Physical Hazard	0
Personal Protection	X

Caution: HMIS[®] rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS[®] rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS[®] rating is to be used with a fully implemented HMIS[®] program. HMIS[®] is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS[®] attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 12/20/2013

Material number: 469589