Revision Date 03/19/2014 Print Date 03/19/2014

#### 1. Identification

Product name Seam Cleaner

Supplier Sika Corporation

Address 201 Polito Avenue

Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone (201) 933-8800

Telefax (201) 804-1076

Emergency telephone CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the

chemical and restrictions on

For further information, refer to the product technical data

sheet.

#### 2. Hazards identification

use

#### **GHS Classification**

Flammable liquids, Category 2 Eye irritation, Category 2A

Specific target organ systemic toxicity single exposure, Category 3, Central

nervous system

H225: Highly flammable liquid and vapor. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

#### **GHS Label element**

Hazard pictograms





Signal Word Danger

: H225 Highly flammable liquid and vapor. **Hazard Statements** 

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

**Precautionary Statements** : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. -

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Warning

: Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain,liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

See Section 11 for more detailed information on health effects and symptoms.

#### 3. Composition/information on ingredients

#### **Hazardous ingredients**

Chemical Name	CAS-No.	Concentration (%)
acetone	67-64-1	>= 50 - <= 100 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### 4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

Revision Date 03/19/2014 Print Date 03/19/2014

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

: irritant effects

Respiratory disorder Excessive lachrymation

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

#### 5. Fire-fighting measures

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: Water

Specific extinguishing

methods

: Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Remove all sources of ignition.

Deny access to unprotected persons.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Revision Date 03/19/2014 Print Date 03/19/2014

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

#### 7. Handling and storage

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Store in cool place.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : no data available

#### 8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
acetone	67-64-1	ACGIH	TWA	500 ppm
		ACGIH	STEL	750 ppm
		OSHA Z-1	TWA	1,000 ppm 2,400 mg/m3
		OSHA P0	TWA	750 ppm 1,800 mg/m3
		OSHA P0	STEL	1,000 ppm 2,400 mg/m3

## Safety Data Sheet

# Seam Cleaner

Revision Date 03/19/2014 Print Date 03/19/2014

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### \*\*Basis

ACGIH. Threshold Limit Values (TLV)

OSHA Po. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

#### **Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust

concentrations below any lower explosive limits.

#### Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Safety eyewear complying with an approved standard should Eye protection

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

Remove respiratory and skin/eye protection only after vapors

have been cleared from the area.

Remove contaminated clothing and protective equipment

before entering eating areas.

#### 9. Physical and chemical properties

Appearance liquid Color colorless

Odor characteristic

sweet

Odor Threshold no data available

Flash point -4 °F (-20 °C)

869 °F (465 °C) Autoignition temperature

Decomposition temperature no data available

Lower explosion limit (Vol%) 2.5 %(V)

Upper explosion limit (Vol%) 13 %(V)

Flammability (solid, gas) no data available

Oxidizing properties no data available

Autoignition temperature no data available

pΗ ca. 5.5

Melting point/range /

Freezing point

Boiling point/boiling range no data available

Vapor pressure 1.747 mmHg (2.3298 hpa)

0.790 g/cm3 Density

Water solubility Note: completely miscible

Partition coefficient: n-

octanol/water

no data available

no data available

Viscosity, dynamic no data available

Viscosity, kinematic ca.> 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density no data available

Evaporation rate no data available

Burning rate no data available

Volatile organic compounds

(VOC) content

: 0 g/l

#### 10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : no data available

#### 11. Toxicological information

#### **Acute toxicity**

#### **Product**

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

#### Skin corrosion/irritation

#### **Product**

no data available

#### Serious eye damage/eye irritation

#### **Product**

Causes serious eye irritation.

#### Respiratory or skin sensitization

#### **Product**

no data available

#### Germ cell mutagenicity

#### **Product**

Mutagenicity : no data available

#### Carcinogenicity

#### **Product**

Carcinogenicity : no data available

Revision Date 03/19/2014 Print Date 03/19/2014

IARC not applicable NTP not applicable

Reproductive Toxicity/Fertility

**Product** 

Reproductive toxicity : no data available

Reproductive Toxicity/Development/Teratogenicity

**Product** 

Teratogenicity : no data available

STOT-single exposure

**Product** 

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

**Product** 

Assessment: no data available

**Aspiration toxicity** 

**Product** 

no data available

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

Component:

acetone 67-64-1 <u>Toxicity to fish:</u>

LC50 Species: Fish Dose: > 5,000 mg/l Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates:

EC50

Species: Daphnia Dose: 12.700 mg/l Exposure time: 48 h

Toxicity to algae:

ErC50

Species: Pseudokirchneriella subcapitata (green algae)

Dose: > 530 mg/l

Exposure time: 96 h

#### 13. Disposal considerations

#### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

#### 14. Transport information

DOT

UN number 1090 Description of the goods Acetone

Class 3
Packing group II
Labels 3
Emergency Response 127

Guidebook Number

IATA

UN number 1090
Description of the goods Acetone

Class 3
Packing group II
Labels 3
Packing instruction (cargo 364

aircraft)

Packing instruction 353

(passenger aircraft)

Packing instruction Y341

(passenger aircraft)

**IMDG** 

UN number 1090
Description of the goods ACETONE

 Class
 3

 Packing group
 II

 Labels
 3

 EmS Number 1
 F-E

 EmS Number 2
 S-D

Marine pollutant no

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Revision Date 03/19/2014 Print Date 03/19/2014

#### Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

#### 15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

#### **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### **SARA304 Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Clean Air Act

**Ozone-Depletion** 

**Potential** 

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 This product does not contain any chemicals known to the State

of California to cause cancer, birth, or any other reproductive

defects.

#### 16. Other information

Revision Date 03/19/2014

Print Date 03/19/2014

**HMIS Classification** 



**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/19/2014

Material number: 469588