Sikacoat® BC400

Revision Date 9/27/2016 Print Date 9/27/2016

1. Identification

Product name Sikacoat® BC400

Supplier Sika Corporation

Address 201 Polito Avenue

Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone (201) 933-8800

Telefax (201) 804-1076

Emergency telephone CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the

chemical and restrictions on

For further information, refer to the product technical data sheet.

use

2. Hazards identification

GHS Classification

Carcinogenicity, Category 1A H350: May cause cancer.

Specific target organ systemic toxicity -H373: May cause damage to organs through repeated exposure, Category 2, Kidney prolonged or repeated exposure.

, Liver

GHS Label element

Hazard pictograms

Signal Word Danger

Hazard Statements : H350 May cause cancer.

H373 May cause damage to organs (Kidney, Liver) through

prolonged or repeated exposure.

: Prevention: **Precautionary Statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P281 Use personal protective equipment as required.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention. Storage: Revision Date 9/27/2016

Print Date 9/27/2016

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Quartz (SiO2)	14808-60-7	>= 10 - < 20 %
Titanium dioxide	13463-67-7	>= 5 - < 10 %
ethanediol	107-21-1	>= 2 - < 5 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: carcinogenic effects

See Section 11 for more detailed information on health effects

and symptoms.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

Revision Date 9/27/2016 Print Date 9/27/2016

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment. Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage

Prevent unauthorized access.

Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : no data available

8. Exposure controls/personal protection

Sikacoat® BC400

Revision Date 9/27/2016 Print Date 9/27/2016

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO2)	14808-60-7	ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-3	TWA	30 mg/m3/%SiO2+2 total dust
		OSHA Z-3	TWA	10 mg/m3/%SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf/%SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
titanium dioxide	13463-67-7	ACGIH	TWA	10 mg/m3
		OSHA P0	TWA	10 mg/m3 Total
		OSHA Z-1	TWA	15 mg/m3 total dust
ethanediol 107-2	107-21-1	OSHA P0	С	50 ppm 125 mg/m3
		ACGIH	С	100 mg/m3

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any

recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

Revision Date 9/27/2016

Print Date 9/27/2016

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Wash hands before breaks and immediately after handling the

product

Remove contaminated clothing and protective equipment

before entering eating areas.

9. Physical and chemical properties

Appearance : viscous liquid

Color : opaque

Odor : mild

Odor Threshold : no data available

Flash point : ca. $> 212 \,^{\circ}\text{F} \, (> 100 \,^{\circ}\text{C})$

Ignition temperature : not applicable

Decomposition temperature : no data available

Lower explosion limit (Vol%) : no data available

Upper explosion limit (Vol%) : no data available

Flammability (solid, gas) : no data available

Oxidizing properties : no data available

Autoignition temperature : no data available

pH : Note: not applicable

Melting point/range /

Freezing point

: no data available

Boiling point/boiling range

no data available

Print Date 9/27/2016

Vapor pressure no data available

Density ca.1.03 g/cm3

at 73 °F (23 °C)

Water solubility Note: soluble

Partition coefficient: n-

octanol/water

no data available

Viscosity, dynamic no data available

Viscosity, kinematic : ca.> 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density : no data available

no data available Evaporation rate

Burning rate no data available

Volatile organic compounds

(VOC) content

20 g/l

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : no data available

: no data available Incompatible materials

11. Toxicological information

Acute toxicity

Product

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

Skin corrosion/irritation

Product

no data available

Serious eye damage/eye irritation

Product

no data available

Respiratory or skin sensitization

Product

no data available

Germ cell mutagenicity

Product

Mutagenicity : no data available

Carcinogenicity

Product

Carcinogenicity : May cause cancer.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

Group 2B: Possibly carcinogenic to humans titanium dioxide 13463-67-7

Known to be human carcinogen

Quartz (SiO2) 14808-60-7

Reproductive Toxicity/Fertility

Product

NTP

Reproductive toxicity : no data available

Reproductive Toxicity/Development/Teratogenicity

Product

Teratogenicity : no data available

STOT-single exposure

Product

Assessment: no data available

STOT-repeated exposure

Product

Assessment: no data available

Aspiration toxicity

Product

no data available

Revision Date 9/27/2016 Print Date 9/27/2016

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

13. Disposal considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

15. Regulatory information

TSCA list : On TSCA Inventory

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

Print Date 9/27/2016

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

ethanediol 107-21-1 2.00 %

Clean Air Act

Ozone-Depletion

Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR

ethanediol

107-21-1

2.00 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

California Prop 65 WARNING! This product contains a chemical known in the

State of California to cause cancer.

16. Other information

HMIS Classification



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS[®] rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

Revision Date 9/27/2016 Print Date 9/27/2016

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 9/27/2016

Material number: 447123