

**JM EPDM LAP CAULK**

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : JM EPDM LAP CAULK

Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127

Telephone : 303-978-2000 8:00AM-5:00PM M-F  
Emergency telephone : 1-800-424-9300 (Chemtrec, in English)  
number

Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 2

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3  
- single exposure

Skin sensitisation : Category 1

**GHS Label element**

Hazard pictograms



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer if inhaled.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

## JM EPDM LAP CAULK

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ eye protection/ face protection.  
 P272 Contaminated work clothing should not be allowed out of the workplace.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous components**

Chemical Name	CAS-No.	Concentration (%)
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 20 - < 30
Stoddard solvent	8052-41-3	>= 10 - < 20
kaolin	1332-58-7	>= 5 - < 10
Mineral Oil	Not Assigned	>= 5 - < 10

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Symptoms of poisoning may appear several hours later.  
 Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
 If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
 If on clothes, remove clothes.

**JM EPDM LAP CAULK**

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

- In case of eye contact : Remove contact lenses.  
Immediately flush eye(s) with plenty of water.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform

## JM EPDM LAP CAULK

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.  
 Do not breathe vapours/dust.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Open drum carefully as content may be under pressure.  
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Solvent naphtha (petroleum), light aliph.	64742-89-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m <sup>3</sup>	NIOSH REL
		C	1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,900 mg/m <sup>3</sup>	OSHA
		TWA	100 ppm 525 mg/m <sup>3</sup>	OSHA
kaolin	1332-58-7	TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH

**JM EPDM LAP CAULK**

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (Total dust)	10 mg/m3	OSHA
		TWA (respirable dust fraction)	5 mg/m3	OSHA
Mineral Oil	Not Assigned	(Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
		PEL (Mist)	5 mg/m3	OSHA
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
carbon black (extracts)	1333-86-4	TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA
		TWA	3.5 mg/m3	OSHA
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
		TWA (Inhalable fraction)	3 mg/m3	ACGIH
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA
		TWA (Total dust)	10 mg/m3	OSHA
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection  
Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Eye protection : Tightly fitting safety goggles
- Skin and body protection : impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.  
Written instructions for handling must be available at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**JM EPDM LAP CAULK**

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

Appearance	: paste
Colour	: black
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 85 °C (1,013.33 hPa)
Flash point	: 10 °C estimated
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 8 %(V)
Lower explosion limit	: 1 %(V)
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.988 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	
Water solubility	: practically insoluble
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: ca. 600,000 mPa.s (20 °C)
Viscosity, kinematic	: > 7 mm <sup>2</sup> /s (40 °C)

**SECTION 10. STABILITY AND REACTIVITY**

**JM EPDM LAP CAULK**

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : 11333 ppm Exposure time: 4 h Test atmosphere: gas Method: Calculation method

**Acute toxicity****Components:****Solvent naphtha (petroleum), light aliph.:**

Acute oral toxicity	: LD50 (Rat): > 8,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 3400 ppm Exposure time: 4 h
Acute dermal toxicity	: LD50 (Rat): > 4,000 mg/kg

**Acute toxicity****kaolin:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg

**Acute toxicity****Mineral Oil:**

Acute oral toxicity	: LD50 Oral (Rat): 50,000 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rat): > 2,000 mg/kg

**Germ cell mutagenicity****Components:****Solvent naphtha (petroleum), light aliph.:**

Germ cell mutagenicity-	: In vivo tests showed mutagenic effects
-------------------------	--

**JM EPDM LAP CAULK**

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

Assessment

**Carcinogenicity****Components:****Solvent naphtha (petroleum), light aliph.:**

Carcinogenicity - Assessment : Possible human carcinogen

**IARC**

Group 1: Carcinogenic to humans

kaolin 1332-58-7

Group 2B: Possibly carcinogenic to humans

carbon black (extracts) 1333-86-4

titanium dioxide 13463-67-7

**ACGIH**

Confirmed animal carcinogen with unknown relevance to humans

carbon black (extracts) 1333-86-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

Known to be human carcinogen

kaolin 1332-58-7

**Aspiration toxicity****Components:****Solvent naphtha (petroleum), light aliph.:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available



## JM EPDM LAP CAULK

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation : 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

Disposal of residual product : Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Do not re-use empty containers.  
 Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

**International transport regulations**

US DOT: UN1133 Adhesive, 3, II Limited Quantity

### SECTION 15. REGULATORY INFORMATION

TSCA list : Not relevant

Not relevant

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
benzene	71-43-2	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

**JM EPDM LAP CAULK**

Version 1.3

Revision Date 05/29/2015

Print Date 05/29/2015

This material does not contain any components with a section 304 EHS RQ.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM1 Intermediate or Final VOC's (40 CFR 60.489).

**California Prop 65**

WARNING! This product contains a chemical known to the State of California to cause cancer.

carbon black (extracts)	1333-86-4
titanium dioxide	13463-67-7
Crystalline silica	14808-60-7
ethylbenzene	100-41-4
benzene	71-43-2
naphthalene	91-20-3

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

benzene	71-43-2
toluene	108-88-3

**The components of this product are reported in the following inventories:**

**TSCA** : Listed on TSCA  
: Mineral Oil  
: POLYMER

**DSL** : All components of this product are on the Canadian DSL.  
: Mineral Oil  
: POLYMER

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date : 05/29/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.